

Wooden Doors

include flush solid core MDF door, pine frame, stainless steel spring hinges, brushed nickel door handle, Porta lock¹ for home elevators or WR-500² for VPLs; 80" high by 36" wide (42" option for flat doors)



Flat



Flat Vision Panel



2-Panel



5-Panel

ProDoor

fire rated 1.5 hour UL certified;
includes Prolock, WR-500 lock or GAL
for VPLs²; Porta lock¹ for residential

- Optional insulated exterior package with concealed operator WR-500 lock
- Custom sizes from 32" to 48" wide, and up to 96" high



Aluminum Door

flush low profile with stainless steel hinges



For home elevators: tempered laminated safety glass insert, spring hinges and Porta¹ or SDL lock³ (shown); painted white (PS111W2)



For VPLs: acrylic, tempered glass or laminated safety glass insert and WR-500 or GAL lock² for VPLs

- ¹ Porta lock is compliant with code ASME A17.1 for home elevators
- ² WR-500, Prolock and GAL locks are compliant with code ASME A18.1 for VPLs
- ³ SDL is compliant with code ASME A17.1 for home elevators

Frame and Lock Kits

for use with flush solid core slab doors by others



Frame and Lock

for home elevators with 1¾" door; includes pine frame 80" wide by 36" or 42" wide; stainless steel spring hinges, Porta lock¹

Porta Lock

for home elevators¹



WR-500 Lock

weather-resistant lock for VPLs²

